



ROAD TYPE	POSTED SPEED	MIN. TAPER LENGTH (L)	LENGTH OF BUFFER (BZ)	MIN. SIGN SPACING (SS)				ONE LANE TWO-WAY FLAGGING
		12 FT LANE CLOSURE	DESIREABLE	A	B	C	D	TAPER LENGTH
		FT	FT	FT	FT	FT	FT	FT
CONVENTIONAL	30	180	200	100	100	100	100	50
	35	245	250	350	350	350	175	
	40	320	305					
	45	540	360	500	500	500	250	
	50	600	425					
	55	660	495					
	60	720	570					
FREEWAY	65	780	645	1000	1640	2640	500	[Grid Pattern]
	70	840	730					
	75	900	820					
	80	960	910					

Date: 09/01/2020 **Author:** MIKE **Project:** PCI- WILSON DR. 2440 S., HURRICANE

Comments:
 COMPANY: PCI
 CONTACT: WAYNE
 LOCATION: 2440 S. WILSON DR., HURRICANE
 APPLICATION: SOFT ROAD CLOSURE

NOTES:
 - TCP SPECIFIC TO LOCATION ONLY; NOT TO SCALE.
 - SPACING BASED ON 30 MPH; SEE SPACING CHART.
 - TCT OR TCS ONLY.